



Operation

- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure mounted on rollers for flexible use
- Large shelf hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

Technical features

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel



3.8 mm Strips

Cutting mechanism is insensitive to

Paper clips yes
CDs/DVDs yes
3.5" floppy disks no
Credit cards yes
Passports no





Performances intimus 452

Size of shreds	3.8 mm
Shredding capacity*	15 -17 sheets
Security level DIN 32757	level 2
Working width	405 mm
Cutting speed	0.25 m/sec.
Catchbasket / Volume	113
Noise level	53 dB(A)
Dimensions W / D / H	66/43/88 cm
Weight	55 kg

^{*} based on 70g/m² DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply.
Technical changes and colour variances reserved. 1/2004





intimus 452 CC



1.9 x 15 mm Cross Cut

Operation

- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure mounted on rollers for flexible use
- Large shelf hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

Technical features

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel

Cutting mechanism is insensitive to

Paper clips	yes
CDs/DVDs	no
3.5" floppy disks	no
Credit cards	no
Passports	no





Performances intimus 452 CC

1.9 x 15 mm
10 - 12 sheets
level 4
405 mm
0.14 m/sec.
113
53 dB(A)
66/43/88 cm
55 kg
_

^{*} based on 70g/m² DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply.





