



- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

### Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure mounted on rollers for flexible use
- Large-volume catchbasket with changeable, environmentally acceptable PE bag
- Optional: large shelf to save space

### **Technical features**

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel

#### PT 43 23 20 20

5.8 mm Strips

# Cutting mechanism is insensitive to

Paper clips	yes
CDs/DVDs	yes
3.5" floppy disks	no



### Performances intimus 702

Size of shreds	5.8 mm
Shredding capacity*	65 - 70 sheets
Security level DIN 32757	level 2
Working width	405 mm
Cutting speed	0.12 m/sec.
Catchbasket / Volume	175
Noise level	52 dB(A)
Dimensions W / D / H	66/56/105 cm
Weight	90 kg

<sup>t</sup> based on 70g/m<sup>2</sup> DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply.

Technical changes and colour variances reserved. 1/2004







- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

### Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure mounted on rollers for flexible use
- Large shelf hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

### **Technical features**

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel



Strips

# Cutting mechanism is insensitive to

Paper clips	yes
CDs/DVDs	yes
3.5" floppy disks	yes



# Performances intimus 702

Size of shreds	3.8 mm
Shredding capacity*	40 - 45 sheets
Security level DIN 32757	level 2
Working width	405 mm
Cutting speed	0.12 m/sec.
Catchbasket / Volume	175
Noise level	52 dB(A)
Dimensions W / D / H	66/56/105 cm
Weight	90 kg

\* based on 70g/m<sup>2</sup> DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. Technical changes and colour variances reserved. 5/2004









- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

### Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure mounted on rollers for flexible use
- Large shelf hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

### **Technical features**

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel



4 x 46 mm Cross Cut

# Cutting mechanism is insensitive to

Paper clips	yes
CDs/DVDs	yes
3.5" floppy disks	yes



# Performances intimus 702 CC

Size of shreds	4 x 46 mm
Shredding capacity*	50 - 55 sheets
Security level DIN 32757	level 3
Working width	405 mm
Cutting speed	0.1 m/sec.
Catchbasket / Volume	175 l
Noise level	52 dB(A)
Dimensions W / D / H	66/56/105 cm
Weight	90 kg

<sup>t</sup> based on 70g/m<sup>2</sup> DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply.

Technical changes and colour variances reserved. 5/2004







- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

### Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure mounted on rollers for flexible use
- Large shelf hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

### **Technical features**

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel



1.9 x 15 mm Cross Cut

# Cutting mechanism is insensitive to

Paper clips	yes
CDs/DVDs	yes
3.5" floppy disks	yes



# Performances intimus 702 CC

Size of shreds	1.9 x 15 mm
Shredding capacity*	25 - 30 sheets
Security level DIN 32757	level 4
Working width	405 mm
Cutting speed	0.1 m/sec.
Catchbasket / Volume	175
Noise level	52 dB(A)
Dimensions W / D / H	66/56/105 cm
Weight	90 kg

\* based on 70g/m<sup>2</sup> DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. Technical chapage and colour variances recenced. 5/2004.

Technical changes and colour variances reserved. 5/2004







- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

### Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure mounted on rollers for flexible use
- Large shelf hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

### **Technical features**

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel



# Cutting mechanism is insensitive to

Paper clips	no
CDs/DVDs	no
3.5" floppy disks	no



# Performances intimus 702 SF

Size of shreds	0.8 x 4.5 mm
Shredding capacity*	8 - 10 sheets
Security level DIN 32757	level 5
Working width	405 mm
Cutting speed	0.23 m/sec.
Catchbasket / Volume	175
Noise level	52 dB(A)
Dimensions W / D / H	66/56/105 cm
Weight	90 kg

\* based on 70g/m<sup>2</sup> DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. Technical chapage and colour variances recenced. 5/2004.

Technical changes and colour variances reserved. 5/2004

